

# HYCON HH25 BREAKER



## PRODUCT FEATURES

HYCON HH25 is compact and has very high performance in relation to its weight. It is designed for tough jobs of breaking strong concrete, asphalt, frozen ground etc.

HH25 comes standard with the HYCON vibration-reduced handle. It is available both as 20 and 30 l.p.m. models.

It is especially used by contractors, armies, asphalt companies, supply companies, rental etc. Standard tool size is hex 32x160 mm.

The breaker can be connected to the HPP-series and other hydraulic power sources. Other tool sizes are available on request.

## HYDRAULIC BREAKER HH25

Item no. hex 28x160 mm, 30 l.p.m.	1010906
Item no. hex 32x160 mm, 20 l.p.m.	1010025
Item no. hex 32x160 mm, 30 l.p.m.	1010125
Item no. hex 32x152 mm, 20 l.p.m.	1010225
Weight, kg - 20/30 l.p.m.	25,3/25,8
Oil flow, l.p.m. - 20 or 30 l.p.m.	20/30
Working pressure, bar	120
Max pressure, bar	160
Blow frequency, 1/min	1380
Blow energy, J - 20/30 l.p.m.	85/95
Noise level 1m LPA dB -	96
Noise level 1m LWA dB -	108
Vibration level (3 axis) m/s <sup>2</sup>	9,4



Optional:  
Dust suppression kit, Item no. 1113286  
HYCON Water Container, Item no. 3030051

Contact us for more information: [hycon@hycon.dk](mailto:hycon@hycon.dk) / +45 96 47 52 00

## THE HYCON PRODUCT RANGE

CUT-OFF AND RING SAWS • CORE DRILLS • POST DRIVERS • PICK HAMMER • LIGHT & HEAVY DUTY BREAKERS  
SUBMERSIBLE PUMPS • ROCK DRILLS • UNDERWATER EQUIPMENT • GASOLINE, DIESEL AND ELECTRIC POWER PACKS



HYCON A/S  
Juelstrupparken 11  
DK-9530 Støvring

Tel +45 9647 5200  
Fax +45 9647 5201  
[www.hycon.dk](http://www.hycon.dk)

**DISTRIBUTOR:**