

# HYCON HRD30 ROCK DRILL



## PRODUCT FEATURES

The HYCON HRD30 is an “all-in-one” high performing hand-held rock drill designed for the toughest drilling applications in granite and concrete up to 2,4 meters of drilling depths.

Using standard integral drill steel with air-flushing from the integrated compressor combined with a high performing hydraulic impact and rotation unit makes the HRD30 the most effective rock drill available on the market. The airflow of the integrated compressor is sufficient for most standard drilling in granite or concrete.

Compact in size the HRD30 performs in line (or better) with larger pneumatic type drills where costly and large

compressors will make it difficult to get and transport to jobsites.

The HRD30 rock drill is ideal for anchoring holes as well as blast- or splitting holes measuring between 25-50 mm depending on drilling depth. It delivers more precise hole sizes too, which is useful when working with non-dynamite destruction solutions such as expanding smoke cartridges or an expanding cracking agent (Bentonamit).

Simply connect it to one of HYCONs compact hydraulic power packs – and start drilling.

Consult one of our salespersons for recommendations for deeper and wider drilling.

## HYDRAULIC ROCK DRILL HRD30

Item no. HRD28X	1010300		
<b>Technical information</b>		Rotation (Clockwise), r.p.m.	320
Dimensions: LxW, mm/ Weight, kg	708x406/29	Blow frequency, Hz	40
Oil flow, l.p.m.	30	Noise level LWA dB	105
Working pressure, bar	130	Air Flushing, m3/h	10
Max. pressure, bar	172	Vibration level (3 axis) m/s2	13
Drill steel shank size, mm hex	22x108		



Contact us for more information: [hycon@hycon.dk](mailto:hycon@hycon.dk) / +45 96 47 52 00

## THE HYCON PRODUCT RANGE

CUT-OFF AND RING SAWS • CORE DRILLS • POST DRIVERS • PICK HAMMER • LIGHT & HEAVY DUTY BREAKERS  
SUBMERSIBLE PUMPS • ROCK DRILLS • UNDERWATER EQUIPMENT • GASOLINE, DIESEL AND ELECTRIC POWER PACKS



HYCON A/S  
Juelstrupparken 11  
DK-9530 Støvring

Tel +45 9647 5200  
[www.hycon.dk](http://www.hycon.dk)

**DISTRIBUTOR:**